

250W DUAL POWER AMPLIFIER

DA-250DH(CE)

■ DESCRIPTION

The DA-250DH is a 2-Channel Digital Power Amplifier designed for 100 V line high-impedance distribution and features lightweight, compact, high power output, and high efficiency. It delivers 250 W \times 2 channels (40 Ω output) using a switching power supply. Each channel is equipped with an independent power section. It can be electrically isolated from the high-impedance speaker system by attaching the MT-250H Output Transformer (optional). It can be mounted in an EIA Standard equipment rack (1 unit size).

■ SPECIFICATIONS

*0 dB = 0.775 V

| | 000 040 1/ 40 50 /60 11 |
|-----------------------|--------------------------------------------------------------------------------|
| Power Source | 220 - 240 V AC, 50/60 Hz |
| Amplification System | Digital Class D |
| Power Consumption | 120 W (based on EN standards) |
| · | 580 W (rated output 40 Ω $	imes$ 2) |
| Input | 2 circuits, +4 dB* (1.23 V) (input level control in maximum position), |
| <u>'</u> | 10 k Ω , electronically—balanced, removable terminal block (3 pins), |
| | XLR-3-31 type connector |
| | CH 1 mode ON/OFF switch (ON: PARALLEL, OFF: STEREO) |
| Rated Output | 2 channels: 250 W \times 2 (40 Ω) |
| , | M4 screw terminal, distance between barriers: 8.8 mm (0.35") |
| Frequency Response | 50 - 20,000 Hz (-3 dB, +0 dB) |
| Total Harmonic | 0.1% (1 kHz) |
| Distortion | 0.3% (100 - 20,000 Hz) |
| Protection Circuit | Protection against excessive current flow due to overload, short circuit, |
| | unusual DC voltage output, and heat sink temperature rise (over 100°C (212°F)) |
| S/N Ratio | 100 dB (A-weighted) |
| Crosstalk | 70 dB (A-weighted) |
| LED Indicator | Power (blue) × 1, Input (green) × 2, Output (yellow) × 2, Peak (red) × 2, |
| | Protect (red) × 2 |
| Cooling | Forced air cooling |
| Operating Temperature | -10°C to +40°C (14°F to 104°F) |
| Operating Humidity | Under 90% RH (no condensation) |
| Finish | Panel: Aluminum, black, alumite |
| | Case: Plated steel sheet |
| Dimensions | 482 (W) × 44 (H) × 401.8 (D) mm (18.98" × 1.73" × 15.82") |
| Weight | 5.3 kg (11.68 lb) |
| Accessory | Power cord (2 m (6.56 ft)) ···1, Removable terminal plug (3 pins) ···2, |
| | Tamper—proof cap …2, Rack mounting screw (with plain washer) …4 |
| Option | Matching transformer: MT-250H |

APPEARANCE

442 [17.4"]

