| Declaration of Performance |
|---|
| According to the Construction Products Regulation EU no. 305/2011 and no. EU 574/2014 |
| DoP document no. 24-105 |
| 1. Unique identification code of product type. |
| F-03BT-WP-UE, F-03WT-WP-UE, F-05BT-WP-UE, F-05WT-WP-UE, F-08BT-WP-UE, F-08WT-WP-UE |
| 2. Indicated use: |
| Loudspeaker for voice alarm systems |
| 3. Manufacturer: |
| TOA Corporation 7-2-1 Minatojima-Nakamachi, Chuo-ku, Kobe 650-0046, Japan |
| Registered trademark: |
| |
| 4. Authorised representative: |
| TOA Electronics Europe GmbH Süderstraße 282, 20537 Hamburg, Germany |
| 5. System/s of AVCP: |
| System 1 |
| 6a. Harmonised standard: . |
| EN 54:2008 Fire detection and fire alarm systems |
| Part 24: Components of voice alarm systems - Loudspeakers |
| Notified body |
| Centrum Naukowo-Badawcze Ochrony Przeciwpożarowej w Józefowie Notified body number: 1438 |
| |
| |
| Page 1/2 |

Г

7. List of declared performances

| Essential characteristics of the product | Harmonised standard EN 54-24: 2008 | Scope of essential characteristics regarding intended use of product |
|--|--|--|
| Perform | nance under fire conditior |) |
| Frequency response limit | 4.2 | Passed |
| Reproducibility | 5.2 | Passed |
| Rated impedance | 5.3 | Passed |
| Horizontal and vertical coverage angles | 5.4 | Passed |
| Maximum sound pressure level | 5.5 | Passed |
| 0 | perational reliability | |
| Durability | 4.3 | Passed |
| Construction | 4.4 | Passed except §4.4.2 |
| Marking and data | 4.5 | Passed |
| Rated noise power (durability) | 5.6 | Passed |
| Enclosure protection | 5.18 | Passed |
| Durability of operation | onal reliability: Temperatu | re resistance |
| Dry heat (operational) | 5.7 | Passed |
| Dry heat (endurance) | 5.8 | passed |
| Cold (operational) | 5.9 | Passed |
| Durability of opera | ational reliability: humidity | resistance |
| Damp heat, cyclic (operational) | 5.10 | Passed |
| Damp heat, steady state (endurance) | 5.11 | Passed |
| Damp heat, cyclic (endurance) | 5.12 | Passed |
| Durability of opera | tional reliability: corrosior | resistance |
| Sulfur dioxide corrosion | 5.13 | Passed |
| Durability of operational | reliability: impact and vib | ration resistance |
| Shock (operational) | 5.14 | Passed |
| Impact (operational) | 5.15 | Passed |
| Vibration, sinusoidal (operational) | 5.16 | Passed |
| Vibration, sinusoidal (endurance) | 5.17 | Passed |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the representative by:

Daisuke Imagawa (managing director)

D. Imagana

Hamburg, 15.08.2024

Page 2/2