

# IES-2042FX-SS-SC

Industrial Ethernet Switch

IES-2000 series are lite-Managed Redundant Ring Ethernet switches providing Ethernet Redundancy protocol, Configuration can be managed by convenient windows utility. Ideal suited for easy managed Ethernet in many applications.



Article number: IES-2042FXSS-SCQJ  
 Alternative products: IES-2042FX-MM-SC,  
 IES-2060

## Specifications

|                        |   |
|------------------------|---|
| Power source           | 12 - 48 V DC (dual, from VX-2000DS, VX-3000DS, VX-3150DS) |
| Power consumption      | 7 W   |
| Control output         | Fault relay (make, 24 V, 1A)                              |
| Network                | 10/100Base-T(X), 100Base-FX                               |
| Connection             | 4 x RJ45, 2 x SC  |
| Indicator              | Power, fault, link/act for ports                          |
| Dimensions (W x H x D) | 54,2 x 154,4 x 106,1 mm                                   |
| Dimensions (ø x D)     | x 106,1 mm  |
| Operating humidity     | 5% - 95%, non-condensating                                |
| Operating temperature  | -40°C to +70°C  |



VX-3000 Series

# IES-2042FX-SS-SC

Industrial Ethernet Switch

---

Appearance