

N-8640DA

IP Door Station



Article number: N-8640DA QJ
 Alternative products: N-8640DS, N-8650DS

Specifications

| | |
|----------------------------------|--|
| Network | 10BASE-T/100BASE-TX (Automatic-Negotiation) |
| Network protocol | TCP/IP, UDP, ARP, ICMP, HTTP, RTP, IGMP |
| Audio packet transmission system | Unicast, Multicast |
| Voice packet loss recovery | silence insertion |
| Audio delay time | 80 ms, 320 ms (controllable on the software) |
| Audio output | Induction Loop Amplifier: Audible Range: 20 – 30 cm distance from center of N-8640DA |
| Power source | Power supply device that complies with IEEE802.3af standard or 12V DC, supplied from the AC Adapter (option) |
| Frequency response | 300 Hz - 7 kHz |
| Power consumption | 4.2 W (at rated input), 5.2 W (max.) |
| Control output | Relay contact output, 1 channel, withstand voltage: 30 V DC, control current: Max. 500 mA, screw terminal |
| Network | 10BASE-T/100BASE-TX (Automatic-Negotiation) |
| Power source | Power supply device that complies with IEEE802.3af standard or 12V DC, supplied from the AC Adapter (option) |
| Power consumption | 4.2 W (at rated input), 5.2 W (max.) |
| Network protocol | TCP/IP, UDP, ARP, ICMP, HTTP, RTP, IGMP |
| Speech method | Hands-free conversation |
| Audio output | Induction Loop Amplifier: Audible Range: 20 – 30 cm distance from center of N-8640DA |
| Control output | Relay contact output, 1 channel, withstand voltage: 30 V DC, control current: Max. 500 mA, screw terminal |
| Finish | Aluminium, brushed, |
| Operating humidity | 90 % RH or less (no condensation) |
| Operating temperature | -10 °C to +50 °C |



N-8000 Series

N-8640DA

IP Door Station

Appearance