




PC-1868W-EB

Ceiling mount speaker



**Easy installation.
Versatile use.**

sound without compromise

www.toa.eu

PC-1868W-EB

Ceiling mount speaker

Designed for simple installation, the TOA PC-1868W-EB ceiling mount speaker is equipped with a metal grille an ABS resin Baffle. The finely crafted design with thin panel does not detract from venue architecture or interior decor.

The speaker can be easily installed thanks to its spring catch method — this saves time and money. It is ideal for use in any kind of public building where pagings and BGM are broadcasted.

- Flat front panel
- Quick and easy installation
- 12 cm speaker


Specifications

	PC-1868W-EB
Rated Input	6W (for 100V line), 3W (for 70V Line)
Rated Impedance	100V line: 1.7kΩ (6W), 3.3kΩ (3W), 10kΩ (1W) (Internal wiring must be changed) 70V line: 1.7kΩ (3W), 3.3kΩ (1.5W), 10kΩ (0.5W) (Internal wiring must be changed)
Sound Pressure Level	90dB (1W, 1m, 330 – 3,300Hz Pink noise)
Frequency Response	100Hz – 16kHz
Speaker Component	12 cm cone-type
Mounting Method	Spring catch
Applicable Cable	Solid copper wire or 7-core twisted copper wire, More than $\varnothing 0.8$ mm or 0.5 mm ² or more
Finish	Baffle: ABS resin, pure white (RAL 9016 or its equivalent) Grille: Net, pure white, paint (RAL 9016 or its equivalent)
Dimensions	180 x 11 (exposed section) + 110 (D)mm
Dimension for Fixing Hole	$\varnothing 150$ (mounting hole) x 50 (maximum ceiling thickness)mm
Weight	675g (bracket included)

Application examples



Shopping center



Hotels



Schools



Retail stores



Hospitals



Exhibition halls



Mounting diagram

