

RM-200SF

SX-2000 FIREMAN'S MICROPHONE

The RM-200SF is a Fireman's Microphone of the matrix system. It is equipped with an Emergency key, permitting it to be used as a remote microphone for emergency broadcast. Zone selection and microphone announcement can be made at the time of emergency broadcast. It offers a surveillance function to detect failures including microphone element failure. The RM-200SF has three function keys that can be set as individual or group selection keys, and each key is linked with the corresponding two indicators. Connecting the optional RM-210, RM-320F Extension units to the RM-200SF expands the number of function keys and indicators in blocks of ten.



Article number:RM-200SF



RM-200SF

SX-2000 FIREMAN'S MICROPHONE

Specifications

Control keys, buttons and knobs	3 buttons for free assignable functions, 1 emergency button, microphone volume, speaker volume, CPU-off switch
Power source.	24 V DC (operating range: 15 – 40 V DC)
Directivity	Unidirectional
Frequency response.	200 Hz - 15 kHz
Audio output	0 dBV, 600 Ω, balanced
Power source.	24 V DC (operating range: 15 – 40 V DC)
Distortion.	< 1 %
Current consumption (value)	240,0 mA max.
Frequency response.	200 Hz - 15 kHz
S/N ratio.	55 dB(A)
Audio output	0 dBV, 600 Ω, balanced
Control keys, buttons and knobs	3 buttons for free assignable functions, 1 emergency button, microphone volume, speaker volume, CPU-off switch
Current consumption	240 mA max.
Transmission range	max. 1200 m
Key extension	4 RM-320F (VX-3000), 5 RM-210 (SX-2000)
Distortion.	< 1 %
Microphone type.	Dynamic microphone AGC
Directivity	Unidirectional
Finish.	ABS resin, bluish grey (PANTONE 538 or equivalent),



SX-2000 Series

RM-200SF

SX-2000 FIREMAN'S MICROPHONE

Appearance