

DESCRIPTION

The SR-F08 is a 2-way passive speaker system for indoor-use.
Properly-designed built-in passive network provides high quality sound and high output capability.
The speaker can be used for many applications as permanent and temporary installations.

SPECIFICATIONS

System Type	2-way, Passive type, Bass-reflex type
Power Handling Capacity	Continuous pink noise: 120 W Continuous program: 360 W
Rated Impedance	8 Ω
Sensitivity	91 dB (1 W, 1 m)
Frequency Response	65 Hz – 20 kHz
Crossover Frequency	1.5 kHz
Directivity Angle	Horizontal: 90°, Vertical: 60° (Horn at 90° Rotation, Horizontal: 60°, Vertical: 90°)
Speaker Component	Low frequency: 20 cm (8") cone-type High frequency: Compression driver fitted with CD horn
Connector	Neutrik NL4MP $\times$ 2, M4 screw terminal, distance between barriers: 11 mm (0.43")
Finish	Enclosure: Birch plywood, black, polyurea coating Grille: Steel plate, black, 40 % gloss, paint
Dimensions	249 (W) $\times$ 450 (H) $\times$ 243 (D) mm (9.8" $\times$ 17.72" $\times$ 9.57")
Weight	11 kg (24.25 lb)
Option	Speaker mounting bracket: HY-B0801, HY-UH08, HY-UV08 Ceiling mount bracket: HY-C0801 Speaker wall mount bracket: HY-W0801, HY-WM08 Speaker stand: ST-34B

APPEARANCE

