

DESCRIPTION

The SR-F08 is a 2-way passive speaker system for indoor-use. Properly-designed built-in passive network provides high quality sound and high output capability. The speaker can be used for many applications as permanent and temporary installations.

SPECIFICATIONS

| | |
|-------------------------|---|
| System Type | 2-way, Passive type, Bass-reflex type |
| Power Handling Capacity | Continuous pink noise: 120 W Continuous program: 360 W |
| Rated Impedance | 8 Ω |
| Sensitivity | 91 dB (1 W, 1 m) |
| Frequency Response | 65 Hz - 20 kHz |
| Crossover Frequency | 1.5 kHz |
| Directivity Angle | Horizontal: 90°, Vertical: 60° (Horn at 90° Rotation, Horizontal: 60°, Vertical: 90°) |
| Speaker Component | Low frequency: 20 cm (8") cone-type High frequency: Compression driver fitted with CD horn |
| Connector | Neutrik NL4MP × 2, M4 screw terminal, distance between barriers: 11 mm (0.43") |
| Finish | Enclosure: Birch plywood, black, polyurea coating Grille: Steel plate, black, 40 % gloss, paint |
| Dimensions | 249 (W) × 450 (H) × 243 (D) mm (9.8" × 17.72" × 9.57") |
| Weight | 11 kg (24.25 lb) |
| Option | Speaker mounting bracket: HY-B0801, HY-UH08, HY-UV08 Ceiling mount bracket: HY-C0801 Speaker wall mount bracket: HY-W0801, HY-WM08 Speaker stand: ST-34B |

APPEARANCE

