Declaration of Performance

According to the Construction Products Regulation EU no. 305/2011 and no. EU 574/2014

DoP document no. 22-005

1. Unique identification code of product type:

VX-3000DS

consisting of the components:

VX-3000DS CE, CR-27, CR-35, NPL65-12I (Yuasa), VX-3000DS CE-GB CR-40, CR-44, NPL100-12 (Yuasa), VX-3150DS-EB CR-SR821 QJ, NPL130-6FIR (Yuasa), VX-3150DS HCE, CR-SR830 QJ NPL200-6 (Yuasa) CR-15, CR-22, CR-SR840 QJ,

2. Indicated use:

Power Supply Equipment for TOA voice alarm systems

3. Manufacturer:

TOA Corporation

7-2-1 Minatojima-Nakamachi, Chuo-ku, Kobe 650-0046, Japan

Registered trademark:





4. Authorised representative:

TOA Electronics Europe GmbH Süderstraße 282, 20537 Hamburg, Germany

5. System of AVCP:

System 1

6a. Harmonised standard:

EN 54:2008 Fire detection and fire alarm systems

Part 4: Power Supply Equipment: 1997 and

Amendments A1:2002 + A2:2006

Notified body:

asbl ANPI vzw

Notified body number: 1134

7. List of declared performances

| Essential characteristics of the product | Harmonised standard EN 54-16: 2008 | Scope of essential characteristics regarding intended use of product |
|---|--|--|
| Performance under fire condition | | |
| General requirements | § 4 | Passed |
| Functions | § 5 | Passed |
| Materials, design and manufacture | § 6 | Passed |
| Operational reliability | | |
| General requirements | § 4 | Passed |
| Functions | § 5 | Passed |
| Materials, design and manufacture | § 6 | Passed |
| Documentation | § 7 | Passed |
| Marking | § 8 | Passed |
| Test of the charger and the standby power source | § 9.3 | Passed |
| Durability of operational reliability: Temperature resistance | | |
| Cold (operational) | § 9.5 | Passed |
| Damp heat, steady state (operational) | § 9.6 | Passed |
| Durability of operational reliability: Vibration resistance | | |
| Impact (operational) | § 9.7 | Passed |
| Vibration, sinusoidal (operational) | § 9.8 | Passed |
| Vibration, sinusoidal (endurance) | § 9.15 | Passed |
| Durability of operational reliability: Electrical stability | | |
| Mains voltage variations | § 9.9 a) | Passed |
| Mains voltage dips and interruptions | § 9.9 b) | Passed |
| Electrostatic discharges (operational) | § 9.9 c) | Passed |
| Radiated electromagnetic fields | § 9.9 d) | Passed |
| Conducted disturbances induced by electromagnetic fields | § 9.9 e) | |
| Fast transient bursts | § 9.9 f) | Passed |
| Slow high energy transients | § 9.9 g) | Passed |
| Durability of operational reliability: Humidity resistance | | |
| Damp heat, steady state (operational) | § 9.6 | Passed |
| Damp heat, steady state (endurance) | § 9.14 | Passed |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the representative by: Daisuke Imagawa (managing director)

Hamburg, 20.09.2022

D. Imagana